

Screwdriver & Set

KT No. & D1

- Shank material - S2 alloy steel
- Grip material - PP + TPR
- Finishing - Magnet chrome plated with black tip

14A1

- Phillips head, round shank
- DIN ISO 8764

KT NO.	No.	mm		inch		mm	g	mm	mm
14A10132	PH1	80	3-1/8	5.0	60	12 / 96			
14A10214	PH2	38	1-1/2	6.0	45	12 / 144			
14A10204	PH2	100	4	6.0	88	12 / 96			
14A10306	PH3	150	6	8.0	144	12 / 144			



14A2

- Slotted head, round shank
- DIN ISO 2380

KT NO.	mm		inch		mm	mm	mm	g	mm	mm
14A20303	3	1/8	0.6	75	3	3.0	37	12 / 144		
14A20404	4	5/32	0.8	100	4	4.0	56	12 / 96		
14A25504	5.5	5/32	1.0	100	4	5.5	82	12 / 96		
14A25505	5.5	7/32	1.0	125	5	5.5	86	12 / 144		
14A26514	6.5	1/4	1.2	38	1-1/2	6.5	47	12 / 144		
14A26506	6.5	1/4	1.2	150	6	6.5	105	12 / 144		
14A20808	8	5/16	1.6	200	8	8.0	166	12 / 144		



14A8

- Pozidriv head, round shank
- DIN ISO 8764

KT NO.	No.	mm		inch		mm	g	mm	mm
14A80132	PZ1	80	3-1/8	5.0	60	12 / 96			
14A80204	PZ2	100	4	6.0	89	12 / 96			



KT NO.	PC.	Contents	Kg	mm
30106AMRB	6	14A1 PH1 x 80, PH2 x 100	0.56	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		
30116AMRB	6	14A8 PZ1 x 80, PZ2 x 100	0.56	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		
30107AMRB	7	14A1 PH1 x 80, PH2 x 100, PH3 x 150	0.82	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		



Screwdriver & Set

KT No. & D1



- Shank material - S2 alloy steel
- Grip material - PP + TPR
- Finishing - Magnet chrome plated with black tip

14A1



- Phillips head, round shank
- DIN ISO 8764

KT NO.	No.	mm		inch		mm	g	mm	mm
14A10132	PH1	80	3-1/8	5.0	60	12 / 96			
14A10214	PH2	38	1-1/2	6.0	45	12 / 144			
14A10204	PH2	100	4	6.0	88	12 / 96			
14A10306	PH3	150	6	8.0	144	12 / 144			



14A2



- Slotted head, round shank
- DIN ISO 2380

KT NO.	mm		inch		mm	mm	mm	g	mm	mm
14A20303	3	1/8	0.6	75	3	3.0	37	12 / 144		
14A20404	4	5/32	0.8	100	4	4.0	56	12 / 96		
14A25504	5.5	5/32	1.0	100	4	5.5	82	12 / 96		
14A25505	5.5	7/32	1.0	125	5	5.5	86	12 / 144		
14A26514	6.5	1/4	1.2	38	1-1/2	6.5	47	12 / 144		
14A26506	6.5	1/4	1.2	150	6	6.5	105	12 / 144		
14A20808	8	5/16	1.6	200	8	8.0	166	12 / 144		



14A8



- Pozidriv head, round shank
- DIN ISO 8764

KT NO.	No.	mm		inch		mm	g	mm	mm
14A80132	PZ1	80	3-1/8	5.0	60	12 / 96			
14A80204	PZ2	100	4	6.0	89	12 / 96			



KT NO.	PC.	Contents	Kg	mm
30106AMRB	6	14A1 PH1 x 80, PH2 x 100	0.56	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		
30116AMRB	6	14A8 PZ1 x 80, PZ2 x 100	0.56	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		
30107AMRB	7	14A1 PH1 x 80, PH2 x 100, PH3 x 150	0.82	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		



Screwdriver & Set

KT No. & D1



- Shank material - S2 alloy steel
- Grip material - PP + TPR
- Finishing - Magnet chrome plated with black tip

14A1



- Phillips head, round shank
- DIN ISO 8764

KT NO.	No.	mm		inch		mm	g	mm	mm
14A10132	PH1	80	3-1/8	5.0	60	12 / 96			
14A10214	PH2	38	1-1/2	6.0	45	12 / 144			
14A10204	PH2	100	4	6.0	88	12 / 96			
14A10306	PH3	150	6	8.0	144	12 / 144			



14A2



- Slotted head, round shank
- DIN ISO 2380

KT NO.	mm		inch		mm	mm	mm	g	mm	mm
14A20303	3	1/8	0.6	75	3	3.0	37	12 / 144		
14A20404	4	5/32	0.8	100	4	4.0	56	12 / 96		
14A25504	5.5	5/32	1.0	100	4	5.5	82	12 / 96		
14A25505	5.5	7/32	1.0	125	5	5.5	86	12 / 144		
14A26514	6.5	1/4	1.2	38	1-1/2	6.5	47	12 / 144		
14A26506	6.5	1/4	1.2	150	6	6.5	105	12 / 144		
14A20808	8	5/16	1.6	200	8	8.0	166	12 / 144		



14A8



- Pozidriv head, round shank
- DIN ISO 8764

KT NO.	No.	mm		inch		mm	g	mm	mm
14A80132	PZ1	80	3-1/8	5.0	60	12 / 96			
14A80204	PZ2	100	4	6.0	89	12 / 96			



KT NO.	PC.	Contents	Kg	mm
30106AMRB	6	14A1 PH1 x 80, PH2 x 100	0.56	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		
30116AMRB	6	14A8 PZ1 x 80, PZ2 x 100	0.56	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		
30107AMRB	7	14A1 PH1 x 80, PH2 x 100, PH3 x 150	0.82	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		



Screwdriver & Set

KT No. & D1



- Shank material - S2 alloy steel
- Grip material - PP + TPR
- Finishing - Magnet chrome plated with black tip

14A1



- Phillips head, round shank
- DIN ISO 8764

KT NO.	No.	mm		inch		mm	g	mm	mm
14A10132	PH1	80	3-1/8	5.0	60	12 / 96			
14A10214	PH2	38	1-1/2	6.0	45	12 / 144			
14A10204	PH2	100	4	6.0	88	12 / 96			
14A10306	PH3	150	6	8.0	144	12 / 144			



14A2



- Slotted head, round shank
- DIN ISO 2380

KT NO.	mm		inch		mm	mm	mm	g	mm	mm
14A20303	3	1/8	0.6	75	3	3.0	37	12 / 144		
14A20404	4	5/32	0.8	100	4	4.0	56	12 / 96		
14A25504	5.5	5/32	1.0	100	4	5.5	82	12 / 96		
14A25505	5.5	7/32	1.0	125	5	5.5	86	12 / 144		
14A26514	6.5	1/4	1.2	38	1-1/2	6.5	47	12 / 144		
14A26506	6.5	1/4	1.2	150	6	6.5	105	12 / 144		
14A20808	8	5/16	1.6	200	8	8.0	166	12 / 144		



14A8



- Pozidriv head, round shank
- DIN ISO 8764

KT NO.	No.	mm		inch		mm	g	mm	mm
14A80132	PZ1	80	3-1/8	5.0	60	12 / 96			
14A80204	PZ2	100	4	6.0	89	12 / 96			



KT NO.	PC.	Contents	Kg	mm
30106AMRB	6	14A1 PH1 x 80, PH2 x 100	0.56	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		
30116AMRB	6	14A8 PZ1 x 80, PZ2 x 100	0.56	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		
30107AMRB	7	14A1 PH1 x 80, PH2 x 100, PH3 x 150	0.82	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		



Screwdriver & Set

KT No. & D1



- Shank material - S2 alloy steel
- Grip material - PP + TPR
- Finishing - Magnet chrome plated with black tip

14A1



- Phillips head, round shank
- DIN ISO 8764

KT NO.	No.	mm		Inch		mm	g	mm	mm
14A10132	PH1	80	3-1/8	5.0	60	12 / 96			
14A10214	PH2	38	1-1/2	6.0	45	12 / 144			
14A10204	PH2	100	4	6.0	88	12 / 96			
14A10306	PH3	150	6	8.0	144	12 / 144			



14A2



- Slotted head, round shank
- DIN ISO 2380

KT NO.	mm		Inch		mm	mm	mm	g	mm	mm
14A20303	3	1/8	0.6	75	3	3.0	37	12 / 144		
14A20404	4	5/32	0.8	100	4	4.0	56	12 / 96		
14A25504	5.5	5/32	1.0	100	4	5.5	82	12 / 96		
14A25505	5.5	7/32	1.0	125	5	5.5	86	12 / 144		
14A26514	6.5	1/4	1.2	38	1-1/2	6.5	47	12 / 144		
14A26506	6.5	1/4	1.2	150	6	6.5	105	12 / 144		
14A20808	8	5/16	1.6	200	8	8.0	166	12 / 144		



14A8



- Pozidriv head, round shank
- DIN ISO 8764

KT NO.	No.	mm		Inch		mm	g	mm	mm
14A80132	PZ1	80	3-1/8	5.0	60	12 / 96			
14A80204	PZ2	100	4	6.0	89	12 / 96			



KT NO.	PC.	Contents	Kg	mm
30106AMRB	6	14A1 PH1 x 80, PH2 x 100	0.56	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		
30116AMRB	6	14A8 PZ1 x 80, PZ2 x 100	0.56	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		
30107AMRB	7	14A1 PH1 x 80, PH2 x 100, PH3 x 150	0.82	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		



Screwdriver & Set

KT No. & D1



- Shank material - S2 alloy steel
- Grip material - PP + TPR
- Finishing - Magnet chrome plated with black tip

14A1



- Phillips head, round shank
- DIN ISO 8764

KT NO.	No.	mm		Inch		mm	g	mm	mm
14A10132	PH1	80	3-1/8	5.0	60	12 / 96			
14A10214	PH2	38	1-1/2	6.0	45	12 / 144			
14A10204	PH2	100	4	6.0	88	12 / 96			
14A10306	PH3	150	6	8.0	144	12 / 144			



14A2



- Slotted head, round shank
- DIN ISO 2380

KT NO.	mm		Inch		mm	mm	mm	g	mm	mm
14A20303	3	1/8	0.6	75	3	3.0	37	12 / 144		
14A20404	4	5/32	0.8	100	4	4.0	56	12 / 96		
14A25504	5.5	5/32	1.0	100	4	5.5	82	12 / 96		
14A25505	5.5	7/32	1.0	125	5	5.5	86	12 / 144		
14A26514	6.5	1/4	1.2	38	1-1/2	6.5	47	12 / 144		
14A26506	6.5	1/4	1.2	150	6	6.5	105	12 / 144		
14A20808	8	5/16	1.6	200	8	8.0	166	12 / 144		



14A8



- Pozidriv head, round shank
- DIN ISO 8764

KT NO.	No.	mm		Inch		mm	g	mm	mm
14A80132	PZ1	80	3-1/8	5.0	60	12 / 96			
14A80204	PZ2	100	4	6.0	89	12 / 96			



KT NO.	PC.	Contents	Kg	mm
30106AMRB	6	14A1 PH1 x 80, PH2 x 100	0.56	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		
30116AMRB	6	14A8 PZ1 x 80, PZ2 x 100	0.56	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		
30107AMRB	7	14A1 PH1 x 80, PH2 x 100, PH3 x 150	0.82	1 / 12
		14A2 3 x 75, 4 x 100, 5.5 x 125, 6.5 x 150		

