



## Sockets – Wall mounted, with screw terminals


to DIN VDE 0623, EN 60309-2.  Highly resistant to chemicals. Other voltages and frequencies available on request. For drawings and dimensions see page 102 - 110. Products with pilot contact available on request.



**Wall mounted socket**  
external fixing

IP 44  
Std. Pack. Qty: 10  
Drawing: 1 MB 463


A	P	110 V	230 V	400 V	500 V	>50 - 500 V	
		50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100-300 Hz	300-500 Hz
16	3		27001				
16	4			27002	270		
16	5			27004			
32	3		27005				
32	4			27006	27007		
32	5			27008			



**Wall mounted socket**  
internal fixing, 4 p and 5 p sockets  
the enclosure can be turned 180°

IP 44  
Std. Pack. Qty: 10  
Drawing: 1 MB 209


A	P	110 V	230 V	400 V	500 V	>50 - 500 V	
		50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100-300 Hz	300-500 Hz
16	3	100	101	102		2169	2241
16	4	103	104	105	106	107	108
16	5	109	110	111	2000	2188	2199



**Wall mounted socket**  
internal fixing, enclosure base can be  
turned 180°, sockets are designed for  
adding an auxiliary contact switch

IP 44  
Std. Pack. Qty: 10  
Drawing: 1 MB 43


A	P	110 V	230 V	400 V	500 V	>50 - 500 V	
		50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100-300 Hz	300-500 Hz
16	4	3030	303	1418	3032	3035	3028
16	5	3141	3045	1419	3043	3046	3039
32	3	1420	1421	1422		3139	3134
32	4	1423	1424	1425	1426	1427	1428
32	5	1555	155	1557	3152	3154	3149




**Wall mounted socket**  
X-CONTACT®, suitable for through  
wiring, internal fixing, enclosure  
base can be turned 180°

IP 44  
Std. Pack. Qty: 5  
Drawing: 1 MB 213


A	P	110 V	230 V	400 V	500 V	>50 - 500 V	
		50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100-300 Hz	300-500 Hz
63	3	1136A	1137A				
63	4		1140A	1141A	1142A		
63	5		1144A	1145A			



**Wall mounted socket**  
highly resistant to chemicals, with  
2 external fixing points, enclosure  
base can be turned 180°, sockets  
are designed for adding an auxiliary  
contact switch

IP 67   
Std. Pack. Qty: 10  
Drawing: 1 MB 622

A	P	110 V	230 V	400 V	500 V	>50 - 500 V	
		50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100-300 Hz	300-500 Hz
16	3	9300	9301	9302			
16	4	9320	9321	9322	9323	9325	
16	5	9340	9341	93			
32	3	9350	9351	93			
32	4	9370	9371	9372	9373	937	
32	5	9380	9381	9382			



**Wall mounted socket**  
X-CONTACT, internal fixing,  
enclosure base can be turned 180°,  
with 6 fixing points to accommodate  
special terminals

IP 67  
Std. Pack. Qty: 5  
Drawing: 1 MB 112

A	P	110 V	230 V	400 V	500 V	>50 - 500 V	
		50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	50 a. 60 Hz	100-300 Hz	300-500 Hz
63	3	856	128A	129A			
63	4	130A	131A	132A	133A		
63	5	134A	135A	136A	2007A		