

COLSD

コバルトストレートシャンク ロング ドリル

Straight Shank Cobalt Long Drills

切削条件 Cutting Condition ▶▶B-161

HSS Co
工具材料

h8
直径許容差


118°
先端角

26°
~32°
ねじれ角

1.0-13.0
直径範囲

●汎用のコバルトロングドリルです

This is general cobalt HSS long drills for deep holes.



新商品

超硬ドリル

オーダー方法 COLSD 直径 × 全長

単位 (Unit) : mm

ハイスドリル

直径 Dc	全長 L	溝長 ℓ	在庫 Stock
1.0	100	40	
1.1	100		
1.2	100		
1.3	100		
1.4	100		
1.5	100		
1.6	100		
1.6	150		
1.7	100		
1.7	150		
1.8	100		
1.8	150		
1.9	100		
1.9	150		
2.0	100		
2.0	150		
2.0	200		
2.1	100		
2.1	150		
2.1	200		
2.2	100		
2.2	150		
2.2	200		
2.3	100		
2.3	150		
2.3	200		
2.4	100		
2.4	150		
2.4	200		
2.5	100		
2.5	150		
2.5	200		
2.6	100		
2.6	150		
2.6	200		
2.7	100		
2.7	150		
2.7	200		
2.8	100		
2.8	150		
2.8	200		
2.9	100		
2.9	150		
2.9	200		
3.0	100		
3.0	150		
3.0	200		
3.0	250		
3.0	300		
3.1	150		
3.1	200		
3.1	250		
3.1	300		
3.2	150		
3.2	200		
3.2	250		
3.2	300		
3.3	150		
3.3	200		
3.3	250		
3.3	300		
3.4	150		
3.4	200		
3.4	250		
3.4	300		
3.5	150		

タップ

超硬
エンドミル

ハイス
エンドミル

切断工具

パック・
セット商品
その他

精密工具

技術資料
索引

直径 Dc	全長 L	溝長 ℓ	在庫 Stock
3.5	200	150	
3.5	250	175	
3.5	300	200	
3.6	150	75	
3.6	200	150	
3.6	250	175	
3.6	300	200	
3.7	150	75	
3.7	200	150	
3.7	250	175	
3.7	300	200	
3.8	150	75	
3.8	200	150	
3.8	250	175	
3.8	300	200	
3.9	150	75	
3.9	200	150	
3.9	250	175	
3.9	300	200	
4.0	150	100	
4.0	200	150	
4.0	250	175	
4.0	300	200	
4.0	400	300	
4.1	150	100	
4.1	200	150	
4.1	250	175	
4.1	300	200	
4.2	150	100	
4.2	200	150	
4.2	250	175	
4.2	300	200	
4.3	150	100	
4.3	200	150	
4.3	250	175	
4.3	300	200	
4.4	150	100	
4.4	200	150	
4.4	250	175	
4.4	300	200	
4.5	150	100	
4.5	200	150	
4.5	250	175	
4.5	300	200	
4.5	400	300	
4.6	150	100	
4.6	200	150	
4.6	250	175	
4.6	300	200	
4.7	150	100	
4.7	200	150	
4.7	250	175	
4.7	300	200	
4.8	150	100	
4.8	200	150	
4.8	250	175	
4.8	300	200	
4.9	150	100	
4.9	200	150	
4.9	250	175	
4.9	300	200	
5.0	150	100	
5.0	200	150	
5.0	250	175	
5.0	300	200	
5.0	400	300	

直径 Dc	全長 L	溝長 ℓ	在庫 Stock
5.0	500	350	
5.1	150	100	
5.1	200	150	
5.1	250	175	
5.1	300	200	
5.2	150	100	
5.2	200	150	
5.2	250	175	
5.2	300	200	
5.3	150	100	
5.3	200	150	
5.3	250	175	
5.3	300	200	
5.4	150	100	
5.4	200	150	
5.4	250	175	
5.4	300	200	
5.5	150	100	
5.5	200	150	
5.5	250	175	
5.5	300	200	
5.5	400	300	
5.5	500	350	
5.6	150	100	
5.6	200	150	
5.6	250	175	
5.6	300	200	
5.7	150	100	
5.7	200	150	
5.7	250	175	
5.7	300	200	
5.8	150	100	
5.8	200	150	
5.8	250	175	
5.8	300	200	
5.9	150	100	
5.9	200	150	
5.9	250	175	
5.9	300	200	
6.0	150	100	
6.0	200	150	
6.0	250	175	
6.0	300	200	
6.0	400	300	
6.0	500	350	
6.1	150	100	
6.1	200	150	
6.1	250	175	
6.1	300	200	
6.1	400	300	
6.2	150	100	
6.2	200	150	
6.2	250	175	
6.2	300	200	
6.2	400	300	
6.3	150	100	
6.3	200	150	
6.3	250	175	
6.3	300	200	
6.3	400	300	
6.4	150	100	
6.4	200	150	
6.4	250	175	
6.4	300	200	
6.4	400	300	
6.5	150	100	

単位 (Unit) : mm

直径 Dc	全長 L	溝長 ℓ	在庫 Stock
6.5	200	150	
6.5	250	175	
6.5	300	200	
6.5	400	300	
6.5	500	350	
6.6	150	100	
6.6	200	150	
6.6	250	175	
6.6	300	200	
6.6	400	300	
6.7	150	100	
6.7	200	150	
6.7	250	175	
6.7	300	200	
6.7	400	300	
6.8	150	100	
6.8	200	150	
6.8	250	175	
6.8	300	200	
6.8	400	300	
6.9	150	100	
6.9	200	150	
6.9	250	175	
6.9	300	200	
6.9	400	300	
7.0	150	100	
7.0	200	150	
7.0	250	175	
7.0	300	200	
7.0	400	300	
7.0	500	350	
7.0	600	400	
7.1	150	100	
7.1	200	150	
7.1	250	175	
7.1	300	200	
7.1	400	300	
7.2	150	100	
7.2	200	150	
7.2	250	175	
7.2	300	200	
7.2	400	300	
7.3	150	100	
7.3	200	150	
7.3	250	175	
7.3	300	200	
7.3	400	300	
7.4	150	100	
7.4	200	150	
7.4	250	175	
7.4	300	200	
7.4	400	300	
7.5	150	100	
7.5	200	150	
7.5	250	175	
7.5	300	200	
7.5	400	300	
7.5	500	350	
7.6	150	100	
7.6	200	150	
7.6	250	175	
7.6	300	200	
7.6	400	300	
7.7	150	100	
7.7	200	150	
7.7	250	175	
7.7	300	200	
7.7	400	300	
7.8	150	100	
7.8	200	150	
7.8	250	175	
7.8	300	200	
7.8	400	300	
7.9	150	100	
7.9	200	150	
7.9	250	175	
7.9	300	200	
7.9	400	300	
8.0	150	100	

直径 Dc	全長 L	溝長 ℓ	在庫 Stock
8.0	200	150	
8.0	250	175	
8.0	300	200	
8.0	400	300	
8.0	500	350	
8.0	600	400	
8.1	200	150	
8.1	250	175	
8.1	300	200	
8.1	400	300	
8.2	200	150	
8.2	250	175	
8.2	300	200	
8.2	400	300	
8.3	200	150	
8.3	250	175	
8.3	300	200	
8.3	400	300	
8.4	200	150	
8.4	250	175	
8.4	300	200	
8.4	400	300	
8.5	200	150	
8.5	250	175	
8.5	300	200	
8.5	400	300	
8.5	500	350	
8.6	200	150	
8.6	250	175	
8.6	300	200	
8.6	400	300	
8.7	200	150	
8.7	250	175	
8.7	300	200	
8.7	400	300	
8.8	200	150	
8.8	250	175	
8.8	300	200	
8.8	400	300	
8.9	200	150	
8.9	250	175	
8.9	300	200	
8.9	400	300	
9.0	200	150	
9.0	250	175	
9.0	300	200	
9.0	400	300	
9.0	500	350	
9.0	600	400	
9.1	200	150	
9.1	250	175	
9.1	300	200	
9.1	400	300	
9.2	200	150	
9.2	250	175	
9.2	300	200	
9.2	400	300	
9.3	200	150	
9.3	250	175	
9.3	300	200	
9.3	400	300	
9.4	200	150	
9.4	250	175	
9.4	300	200	
9.4	400	300	

直径 Dc	全長 L	溝長 ℓ	在庫 Stock
9.5	200	150	
9.5	250	175	
9.5	300	200	
9.5	400	300	
9.5	500	350	
9.6	200	150	
9.6	250	175	
9.6	300	200	
9.6	400	300	
9.7	200	150	
9.7	250	175	
9.7	300	200	
9.7	400	300	
9.8	200	150	
9.8	250	175	
9.8	300	200	
9.8	400	300	
9.9	200	150	
9.9	250	175	
9.9	300	200	
9.9	400	300	
10.0	200	150	
10.0	250	175	
10.0	300	200	
10.0	400	300	
10.0	500	350	
10.0	600	400	
10.5	200	150	
10.5	250	175	
10.5	300	200	
10.5	400	300	
10.5	500	350	
11.0	200	150	
11.0	250	175	
11.0	300	200	
11.0	400	300	
11.0	500	350	
11.0	600	400	
11.5	200	150	
11.5	250	175	
11.5	300	200	
11.5	400	300	
11.5	500	350	
12.0	200	150	
12.0	250	175	
12.0	300	200	
12.0	400	300	
12.0	500	350	
12.0	600	400	
12.5	200	150	
12.5	250	175	
12.5	300	200	
12.5	400	300	
12.5	500	350	
13.0	200	150	
13.0	250	175	
13.0	300	200	
13.0	400	300	
13.0	500	350	
13.0	600	400	

新商品

超硬ドリル

ハイスドリル

タップ

超硬
エンドミル

ハイス
エンドミル

切断工具

パック・
セット商品
その他

精密工具

技術資料
索引

一般 構造用鋼	炭素鋼	合金鋼 調質鋼	ダイス鋼 プレハードン鋼	高硬度鋼	
SS400	S45C S50C	SCM NAK	30~40 HRC	40~50 HRC	50~65HRC
○	○	○	○	×	×
ステンレス鋼		Ti 合金 耐熱合金	鋳鉄	アルミ合金	銅合金
SUS304 SUS316	SUS420	Ti / Ni Alloy	FC / FCD	AC / ADC	Cu
○	○	—	○	○	○

○:最適 Excellent ○:適用 Good ×:不適 Not Used —:推奨しません Not recommended

