



Cordless Impact Driver DTD172

Impact force change with one hand
The level of impact force changes every time you press the quick mode-switching button while holding the grip.

Memory function of impact mode is equipped.
If any two modes are registered in advance, you can switch to your desired mode by just pressing quick mode-switching button.



4-stage impact power selection

Max / Hard / Medium / Soft

No load speed / Impacts per min
Max: 0 - 3,600 / 0 - 3,800
Hard: 0 - 3,200 / 0 - 3,600
Medium: 0 - 2,100 / 0 - 2,600
Soft: 0 - 1,100 / 0 - 1,100



Accessories

Tool hanger set

Part No. 197043-2



enables to hook the machine quickly on a snap hook of waist belt.

Charging Time

Battery Model	Fast Charging		
	DC18RC	DC18RD	DC18SD
BL1815N 1.5Ah	15 min		30 min
BL1820B 2.0Ah	24 min		45 min
BL1830B 3.0Ah	22 min		60 min
BL1840B 4.0Ah	36 min		90 min
BL1850B 5.0Ah	45 min		110 min
BL1860B 6.0Ah	55 min		130 min



King of Impact

Max. fastening torque
180 N·m

Overall length
114 mm

Cordless Impact Driver

DTD172RTE/ DTD172Z

Variable Speed	Capacity	Machine Screw: M4 - M8 (5/32 - 5/16") Standard Bolt: M5 - M16 (3/16 - 5/8") High Strength Bolt: M5 - M14 (3/16 - 9/16") Coarse thread (in length): 22 - 125 mm (7/8 - 4-7/8")
Brake	Hex Shank	6.35 mm (1/4")
Reversing	No Load Speed (RPM)	Max / Hard / Mid / Soft / Wood / Bolt / T (1) / T (2) mode: 0 - 3,600 / 3,200 / 2,100 / 1,100 / 1,800 / 3,600 / 2,900 / 3,600
Electronic 4-Speed	Impacts Per Minute (IPM)	Max / Hard / Mid / Soft / Wood / Bolt / T (2) mode: 0 - 3,800 / 3,600 / 2,600 / 1,100 / 3,800 / 3,800 / 2,600
Built-in Job Light	Max Fastening Torque	180 N·m (1,590 in.lbs.)
Carrying Case	Fastening Torque	Hard / Mid / Soft: 170 / 50 / 20 N·m (1,510 / 440 / 180 in.lbs.)
	Vibration Level	Impact tightening of fasteners of the maximum capacity of the tool: 13.5 m/s ²
	Sound Pressure Level	97 dB(A)
	Sound Power Level	108 dB(A)
	Dimensions (L x W x H)	w/o Battery: 114 x 81 x 189 mm (4-1/2 x 3-3/16 x 7-7/16") w/ BL1830B / BL1840B / BL1850B / BL1860B: 114 x 81 x 236 mm (4-1/2 x 3-3/16 x 9-1/4")
	Net weight	1.2 - 1.5 kg (2.6 - 3.3 lbs.)
		DTD172RTE: 2 battery 5.0Ah BL1850B, fast charger DC18RC DTD172Z: Battery & charger are sold separately

Standard Equipment: (+) Truss head screw M4X12 (266622-8), hook (346317-0), twist Torsion bit (+)(-) 65mm (E-10833).

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.

CÔNG TY TNHH MAKITA VIỆT NAM

Kho 456, Block 16, 18L1-2 Đường số 3, KCN VSP, P. Hòa Phú, TP. Thủ Dầu Một, Bình Dương
ĐT: 0274 362 8338 - Fax: 0274 362 8339 - Website: www.makita.com.vn

CHI NHÁNH CTY TNHH MAKITA VN TẠI MIỀN BẮC Khu 5, Số 1, Đường Số 6, KCN - BT - DV VSP Bắc Ninh, P. Phú Châu, TP. Từ Sơn, T. Bắc Ninh. ĐT: 0222 376 5942 Fax: 0222 376 5941	TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH ĐÀ NẴNG 102 Triều Nữ Vương, P. Hải Châu 2, Q. Hải Châu, TP. Đà Nẵng. ĐT: 0236 352 5079 / 0236 352 5179 Fax: 0236 352 9478	TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH BUỒN MA THUỘT 88 Lê Đức Thọ, P. Thới Bình, TP. Thuận An, TP. Thuận An, TP. Thuận An, TP. Thuận An. ĐT: 0262 355 4556 Fax: 0262 355 4557	TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH NHÀ TRANG Lô 56-58 đường B6, Khu đô thị Vinh Diễm Trưng, Xã Vinh Ngọc, TP. Nha Trang, T. Khánh Hòa ĐT: 0259 220 0039
TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HÀ NỘI 85 Trường Chinh, P. Phương Liệt, Q. Thanh Xuân, TP. Hà Nội. ĐT: 0243 202 2585	TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH CẦN THƠ 366 Võ Văn Kiệt, Khu Vực 3, P. An Thới, Q. Bình Thủy, TP. Cần Thơ. ĐT: 0292 389 4358 Fax: 0292 389 4359	TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HẢI PHÒNG Số 01 Lê Duẩn, Di An Hoàng Huy Riverside, P. Thượng Lý, Q. Hồng Bàng, TP. Hải Phòng. ĐT: 0225 863 1529	TRUNG TÂM DỊCH VỤ KHÁCH HÀNG CHI NHÁNH HỒ CHÍ MINH Số 12 Trịnh Văn Cấn, P. Cầu Ông Lãnh, Q. 1, TP. Hồ Chí Minh. ĐT: 0283 821 5191



King of Impact

114 mm Overall length

180 N·m Max. fastening torque



Anti-bit wobbling structure

Two ball bearings are used to securely hold the anvil for reduced bit wobbling.

Slim tool body

Tool head slimmer than Predecessor model enables easier screwdriving in tight corners or confined spaces.

New one-touch bit installation

- Reduced resistance allows for easier bit installation.
- Designed to hold the bit more securely.



4 Assist modes

Wood

Tightening long screws.



No load speed / Impacts per min
0 - 1,800 / 0 - 3,800

The tool drives a screw with low-speed rotation at first. After starting to impact, the rotation speed increases and reaches max speed.

Bolt

Loosening bolts.



No load speed / Impacts per min
0 - 3,600 / 0 - 3,800

This mode helps to prevent a bolt from falling off.

T1

Teks screw thin metal
Driving self-drilling screws to a thin metal like a metal stud.



No load speed / Impacts per min
0 - 2,900 / -

The tool stops rotating soon after impact starts.

T2

Teks screw thick metal
Driving self-drilling screws to a thick metal plate with good finish.




No load speed / Impacts per min
0 - 3,600 / 0 - 2,600

This mode helps to prevent the screws from breakage and stripping.

Light mode

- To turn on the light, set F/R change lever in the neutral position and pull the switch trigger. To turn off the light, pull the switch trigger again.
- This mode enables to use DTD172 as a handy light on dark job sites.

Left and right twin LED job lights with preglow and afterglow functions



The light turns off automatically one hour after turned on.