



工具材料 コーティング 直径許容差 先端角 ねじれ角 直径範囲

●鋼、ステンレス鋼、アルミの深い穴や深い位置の穴あけに適したコーティングロングドリルです。

This is general coated drills for deep holes.



3mm以上はタング付き



オーダ方法

GLD 直径 × 全長

単位 (Unit) : mm

直径 Dc	全長 L	溝長 ℓ	在庫 Stock
1.0	100	50	
1.0	150	60	
1.05	100	50	
1.05	150	60	
1.1	100	50	
1.1	150	60	
1.15	100	50	
1.15	150	60	
1.2	100	50	
1.2	150	60	
1.25	100	50	
1.25	150	60	
1.3	100	50	
1.3	150	60	
1.35	100	50	
1.35	150	60	
1.4	100	50	
1.4	150	60	
1.45	100	50	
1.45	150	60	
1.5	100	50	
1.5	150	60	
1.55	100	50	
1.55	150	60	
1.6	100	50	
1.6	150	60	
1.65	100	50	
1.65	150	60	
1.7	100	50	
1.7	150	60	
1.75	100	50	
1.75	150	60	
1.8	100	50	
1.8	150	60	
1.85	100	50	
1.85	150	60	
1.9	100	50	
1.9	150	60	
1.95	100	50	
1.95	150	60	
2.0	100	50	
2.0	125	65	
2.0	150	80	
2.0	200	100	
2.0	250	120	
2.0	300	150	
2.05	100	50	
2.05	150	80	
2.1	100	50	
2.1	125	65	
2.1	150	80	
2.15	100	50	
2.15	150	80	
2.2	100	50	
2.2	125	65	
2.2	150	80	
2.25	100	50	
2.25	150	80	
2.3	100	50	
2.3	125	65	
2.3	150	80	
2.35	100	50	
2.35	150	80	
2.4	100	50	
2.4	125	65	
2.4	150	80	
2.45	100	50	
2.45	150	80	

直径 Dc	全長 L	溝長 ℓ	在庫 Stock
2.5	100	50	
2.5	125	65	
2.5	150	80	
2.5	200	100	
2.5	200	90	
2.5	250	120	
2.55	100	60	
2.55	150	80	
2.6	100	60	
2.6	125	65	
2.6	150	80	
2.65	100	60	
2.65	150	80	
2.7	100	60	
2.7	125	65	
2.7	150	80	
2.75	100	60	
2.75	150	80	
2.8	100	60	
2.8	125	65	
2.8	150	80	
2.85	100	60	
2.85	150	80	
2.9	100	60	
2.9	125	65	
2.9	150	80	
2.95	100	60	
2.95	150	80	
3.0	100	60	
3.0	125	70	
3.0	150	80	
3.0	200	105	
3.0	200	125	
3.0	250	150	
3.0	300	175	
3.0	350	200	
3.0	400	250	
3.05	100	60	
3.05	150	85	
3.1	100	60	
3.1	125	70	
3.1	150	85	
3.15	100	60	
3.15	150	85	
3.2	100	60	
3.2	125	70	
3.2	150	85	
3.25	100	60	
3.25	150	85	
3.3	100	60	
3.3	125	70	
3.3	150	85	
3.35	100	60	
3.35	150	85	
3.4	100	60	
3.4	125	70	
3.4	150	85	
3.45	100	60	
3.45	150	85	
3.5	100	60	
3.5	125	75	
3.5	150	85	
3.5	200	110	
3.5	200	125	
3.5	250	150	
3.5	300	175	
3.5	350	210	

直径 Dc	全長 L	溝長 ℓ	在庫 Stock
3.5	400	250	
3.55	100	60	
3.55	150	90	
3.6	100	60	
3.6	125	75	
3.6	150	90	
3.65	100	60	
3.65	150	90	
3.7	100	60	
3.7	125	75	
3.7	150	90	
3.75	100	60	
3.75	150	90	
3.8	100	60	
3.8	125	75	
3.8	150	90	
3.85	100	60	
3.85	150	90	
3.9	100	60	
3.9	125	75	
3.9	150	90	
3.95	100	60	
3.95	150	90	
4.0	100	60	
4.0	125	75	
4.0	150	90	
4.0	200	120	
4.0	200	125	
4.0	250	150	
4.0	300	175	
4.0	350	210	
4.0	400	260	
4.05	150	90	
4.1	100	60	
4.1	125	75	
4.1	150	90	
4.15	150	90	
4.2	100	60	
4.2	125	75	
4.2	150	90	
4.25	150	90	
4.3	100	60	
4.3	125	75	
4.3	150	90	
4.35	150	90	
4.4	100	60	
4.4	125	75	
4.4	150	90	
4.45	150	90	
4.5	100	60	
4.5	125	75	
4.5	150	90	
4.5	200	120	
4.5	200	125	
4.5	250	150	
4.5	300	175	
4.5	350	210	
4.5	400	260	
4.55	150	100	
4.6	100	60	
4.6	125	75	
4.6	150	90	
4.65	150	100	
4.7	100	60	
4.7	125	75	
4.7	150	90	
4.75	150	100	
4.8	100	60	

直径 Dc	全長 L	溝長 ℓ	在庫 Stock
4.8	125	75	
4.8	150	100	
4.85	150	100	
4.9	100	60	
4.9	125	75	
4.9	150	100	
4.95	150	100	
5.0	125	80	
5.0	150	110	
5.0	200	125	
5.0	250	150	
5.0	300	175	
5.0	350	210	
5.0	400	260	
5.05	150	100	
5.1	125	80	
5.1	150	110	
5.1	200	125	
5.2	125	80	
5.2	150	110	
5.2	200	125	
5.3	125	80	
5.3	150	110	
5.3	200	125	
5.4	125	80	
5.4	150	110	
5.4	200	125	
5.5	125	80	
5.5	150	110	
5.5	200	125	
5.5	250	150	
5.5	300	175	
5.5	350	210	
5.5	400	260	
5.6	125	80	
5.6	150	110	
5.6	200	125	
5.7	125	80	
5.7	150	110	
5.7	200	125	
5.8	125	80	
5.8	150	110	
5.8	200	125	
5.9	125	80	
5.9	150	110	
5.9	200	125	
6.0	125	90	
6.0	150	110	
6.0	200	125	
6.0	250	150	
6.0	300	175	
6.0	350	210	
6.0	400	260	
6.1	125	90	
6.1	150	110	
6.1	200	125	
6.1	300	175	
6.2	125	90	
6.2	150	110	
6.2	200	125	
6.2	300	175	
6.3	125	90	
6.3	150	110	
6.3	200	125	
6.3	300	175	
6.4	125	90	
6.4	150	110	
6.4	200	125	



工具材料 コーティング 直径許容差 先端角 ねじれ角 直径範囲

低炭素鋼 軟鋼 SS400, S10C ~150HB	炭素鋼 合金鋼 S45C, SCM440 ~225HB	プレハードン鋼 高合金鋼 SUJ, NAK ~275HB	調質鋼 SKD, SKH 30~40HRC	焼入鋼 Hardened Steels 40~50HRC
◎	◎	◎	○	×
ステンレス鋼		耐熱合金	鋳鉄	アルミ合金 銅合金
SUS304	SUS420	Ti/Ni Alloys	FC/FCD	Al/Cu
○	○		○	○

◎:最適 Excellent ○:適用 Good ×:不適 Not Used 無印 (No mark):推奨しません Not recommended

単位 (Unit) : mm

前頁

直径 Dc	全長 L	溝長 ℓ	在庫 Stock
6.4	300	175	
6.5	125	90	
6.5	150	110	
6.5	200	125	
6.5	250	150	
6.5	300	175	
6.5	350	210	
6.5	400	260	
6.6	125	90	
6.6	150	110	
6.6	200	125	
6.6	300	175	
6.7	125	90	
6.7	150	110	
6.7	200	125	
6.7	300	175	
6.8	125	90	
6.8	150	110	
6.8	200	125	
6.8	300	175	
6.9	125	90	
6.9	150	110	
6.9	200	125	
6.9	300	175	
7.0	125	90	
7.0	150	110	
7.0	200	125	
7.0	250	150	
7.0	300	175	
7.0	350	210	
7.0	400	260	
7.1	150	110	
7.1	200	125	
7.1	300	175	
7.2	150	110	□
7.2	200	125	
7.2	300	175	
7.3	150	110	
7.3	200	125	
7.3	300	175	
7.4	150	110	
7.4	200	125	
7.4	300	175	
7.5	150	110	
7.5	200	125	
7.5	250	150	
7.5	300	175	
7.5	350	210	
7.5	400	260	
7.6	150	110	
7.6	200	125	
7.6	300	175	
7.7	150	110	
7.7	200	125	
7.7	300	175	
7.8	150	110	
7.8	200	125	
7.8	300	175	
7.9	150	110	
7.9	200	125	
7.9	300	175	
8.0	150	110	
8.0	200	125	
8.0	250	150	
8.0	300	175	
8.0	350	210	
8.0	400	260	
8.1	150	110	

直径 Dc	全長 L	溝長 ℓ	在庫 Stock
8.1	200	125	
8.1	300	175	
8.2	150	110	
8.2	200	125	
8.2	300	175	
8.3	150	110	
8.3	200	125	
8.3	300	175	
8.4	150	110	
8.4	200	125	
8.4	300	175	
8.5	150	110	
8.5	200	125	
8.5	250	150	
8.5	300	175	
8.5	350	210	
8.5	400	260	
8.6	150	110	
8.6	200	125	
8.6	300	175	
8.7	150	110	
8.7	200	125	
8.7	300	175	
8.8	150	110	
8.8	200	125	
8.8	300	175	
8.9	150	110	
8.9	200	125	
8.9	300	175	
9.0	150	110	
9.0	200	125	
9.0	250	150	
9.0	300	175	
9.0	350	210	
9.0	400	260	
9.1	150	110	
9.1	200	125	
9.1	300	175	
9.2	150	110	
9.2	200	125	
9.2	300	175	
9.3	150	110	
9.3	200	125	
9.3	300	175	
9.4	150	110	
9.4	200	125	
9.4	300	175	
9.5	150	110	
9.5	200	125	
9.5	250	150	
9.5	300	175	
9.5	350	210	
9.5	400	260	
9.6	150	110	
9.6	200	125	
9.6	300	175	
9.7	150	110	
9.7	200	125	
9.7	300	175	
9.8	150	110	
9.8	200	125	
9.8	300	175	
9.9	150	110	
9.9	200	125	
9.9	300	175	
10.0	150	110	
10.0	200	125	
10.0	250	150	

直径 Dc	全長 L	溝長 ℓ	在庫 Stock
10.0	300	175	
10.0	350	210	
10.0	400	260	
10.1	200	125	
10.1	250	150	
10.1	300	175	
10.2	200	125	
10.2	250	150	
10.2	300	175	
10.3	200	125	
10.3	250	150	
10.3	300	175	
10.4	200	125	
10.4	250	150	
10.4	300	175	
10.5	200	125	
10.5	250	150	
10.5	300	175	
10.5	350	210	
10.5	400	260	
10.6	200	125	
10.6	250	150	
10.6	300	175	
10.7	200	125	
10.7	250	150	
10.7	300	175	
10.8	200	125	
10.8	250	150	
10.8	300	175	
10.9	200	125	
10.9	250	150	
10.9	300	175	
11.0	200	125	
11.0	250	150	
11.0	300	175	
11.0	350	210	
11.0	400	260	
11.1	250	150	
11.1	300	175	
11.2	250	150	
11.2	300	175	
11.3	250	150	
11.3	300	175	
11.4	250	150	
11.4	300	175	
11.5	200	125	
11.5	250	150	
11.5	300	175	
11.5	350	210	
11.5	400	260	
11.6	250	150	
11.6	300	175	
11.7	250	150	
11.7	300	175	
11.8	250	150	
11.8	300	175	
11.9	250	150	
11.9	300	175	
12.0	200	125	
12.0	250	150	
12.0	300	175	
12.0	350	210	
12.0	400	260	
12.1	250	150	
12.1	300	175	
12.2	250	150	
12.2	300	175	
12.3	250	150	

直径 Dc	全長 L	溝長 ℓ	在庫 Stock
12.3	300	175	
12.4	250	150	
12.4	300	175	
12.5	200	125	
12.5	250	150	
12.5	300	175	
12.5	350	210	
12.5	400	260	
12.6	250	150	
12.6	300	175	
12.7	250	150	
12.7	300	175	
12.8	250	150	
12.8	300	175	
12.9	250	150	
12.9	300	175	
13.0	200	125	
13.0	250	150	
13.0	300	175	
13.0	350	210	□
13.0	400	260	
13.5	250	150	
13.5	300	200	
14.0	250	150	
14.0	300	200	
14.5	250	150	
14.5	300	200	
15.0	250	150	
15.0	300	200	
16.0	250	150	
16.0	300	200	
17.0	250	150	
17.0	300	200	
18.0	250	150	
18.0	300	200	
19.0	250	150	
19.0	300	200	
20.0	250	150	
20.0	300	200	

□は特定代理店在庫品です。  
Available for Japan customers only.

総目次

G

穴深さ

~3D

~5D

~8D

深穴

フラット・  
塵ぐり

センタ  
リング

ノス  
ドリル

鉄骨

油穴付き

アルミ・  
非鉄金属

ストレート

テーパ

