

# GENERIC TUBE



*Use of genuine Max ink ribbon and Generic tube is recommended. Max shall not be liable for any damage to 3880E/390A/550A caused by the malfunction of non-genuine consumables*

## SPECIFICATIONS

Model	Color	Temperature rating	Voltage rating	Size	Length	For wire
LM-TU315N	WHITE	105°C	600V	ø 1.5mm	100m	< 0.5 mm <sup>2</sup>
LM-TU320N	WHITE	105°C	600V	ø 2.0mm	100m	< 0.5 mm <sup>2</sup>
LM-TU325N	WHITE	105°C	600V	ø 2.5mm	100m	0.5-0.75 mm <sup>2</sup>
LM-TU332N	WHITE	105°C	600V	ø 3.2mm	100m	0.5-1.5 mm <sup>2</sup>
LM-TU336N	WHITE	105°C	600V	ø 3.6mm	100m	1.5-2.5 mm <sup>2</sup>
LM-TU342N	WHITE	105°C	600V	ø 4.2mm	100m	2.5-4.0 mm <sup>2</sup>
LM-TU346N	WHITE	105°C	600V	ø 4.6mm	85m	2.5-4.0 mm <sup>2</sup>
LM-TU352N	WHITE	105°C	600V	ø 5.2mm	65m	4.0-6.0 mm <sup>2</sup>
LM-TU360N	WHITE	105°C	600V	ø 6.0mm	45m	4.0-6.0 mm <sup>2</sup>
LM-TU364N	WHITE	105°C	600V	ø 6.4mm	40m	6.0-10.0 mm <sup>2</sup>
LM-TU370N	WHITE	105°C	600V	ø 7.0mm	40m	6.0-10.0 mm <sup>2</sup>
LM-TU380N	WHITE	105°C	600V	ø 8.0mm	35m	10.0-16.0 mm <sup>2</sup>
LM-TU390N	WHITE	105°C	600V	ø 9.0mm	30m	16.0-35.0 mm <sup>2</sup>
LM-TU3100N	WHITE	105°C	600V	ø 10.0mm	30m	16.0-35.0 mm <sup>2</sup>