



Product Description

MASTER PL-C 2 Pin

Energy-saving compact fluorescent lamps. Compact long-arc low-pressure mercury discharge lamp. Envelope consists of 4 parallel narrow fluorescent tubes

Benefits

- Optimal light performance for short or long operation per switch-on
- Optimal light performance for short or long operation per switch on
- Multiple light color choice
- Long life and sustainable light output
- Good color rendering (CRI >80)

Features

- 2-pin base with a housing incorporating the special instant starter
- 2-pin base with a housing incorporating the special instant starter and capacitor
- Fluorescent tri-phosphor technology
- Lamp characteristics are influenced by operating conditions and control gear used
- Low light depreciation over lamp life
- Dimming is not possible

Application

- Designed for general or supplementary lighting in professional or home environments
- Designed for general or supplementary lighting in professional or home environments
- Recessed or surface-mounted downlighters, wall units, table lamps and pendant lamps
- Recessed or surface-mounted downlighters, wall units, table lamps and pendant lamps

MASTER PL-C 2 Pin

Warnings and Safety


- Use only with electromagnetic control gear
- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Versions



LPPR PLC2P 26W

Dimensional drawing



Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-C 10W/827/2P 1CT/ 5X10BOX	27.1 mm	27.1 mm	75.5 mm	95.0 mm	117.4 mm
MASTER PL-C 10W/865/2P 1CT/ 5X10BOX	27.1 mm	27.1 mm	75.5 mm	95.0 mm	117.4 mm
MASTER PL-C 13W/827/2P 1CT/ 5X10BOX	27.1 mm	27.1 mm	97.5 mm	117.0 mm	139.4 mm
MASTER PL-C 13W/830/2P 1CT/ 5X10BOX	27.1 mm	27.1 mm	97.5 mm	117.0 mm	139.4 mm
MASTER PL-C 13W/840/2P 1CT/ 5X10BOX	27.1 mm	27.1 mm	97.5 mm	117.0 mm	139.4 mm
MASTER PL-C 18W/827/2P 1CT/ 5X10BOX	27.1 mm	27.1 mm	109.5 mm	128.0 mm	150.4 mm
MASTER PL-C 18W/830/2P 1CT/ 5X10BOX	27.1 mm	27.1 mm	109.5 mm	128.0 mm	150.4 mm
MASTER PL-C 26W/840/2P 1CT/ 5X10BOX	27.1 mm	27.1 mm	130.5 mm	149.0 mm	171.4 mm
MASTER PL-C 26W/865/2P 1CT/ 5X10BOX	27.1 mm	27.1 mm	130.5 mm	149.0 mm	171.4 mm

MASTER PL-C 2 Pin

Controls and Dimming

Dimmable	No
----------	----

Approval and Application

Mercury (Hg) Content (Nom)	1.4 mg
----------------------------	--------

General Information

Order Code	Full Product Name	Cap-Base
927903882701	MASTER PL-C 10W/827/2P 1CT/5X10BOX	G24D-1
927903886502	MASTER PL-C 10W/865/2P 1CT/5X10BOX	G24D-1
927904882701	MASTER PL-C 13W/827/2P 1CT/5X10BOX	G24D-1
927904883001	MASTER PL-C 13W/830/2P 1CT/5X10BOX	G24D-1
927904884002	MASTER PL-C 13W/840/2P 1CT/5X10BOX	G24D-1

Order Code	Full Product Name	Cap-Base
927905782701	MASTER PL-C 18W/827/2P 1CT/5X10BOX	G24D-2
927905783001	MASTER PL-C 18W/830/2P 1CT/5X10BOX	G24D-2
927906184001	MASTER PL-C 26W/840/2P 1CT/5X10BOX	G24D-3
927906186565	MASTER PL-C 26W/865/2P 1CT/5X10BOX	G24D-3

Light Technical

Order Code	Full Product Name	Color Designation	Correlated	
			Color Temperature (Nom)	Luminous Efficacy (rated) (Nom)
927903882701	MASTER PL-C 10W/827/2P 1CT/5X10BOX	Incandescent White	2700 K	60 lm/W
927903886502	MASTER PL-C 10W/865/2P 1CT/5X10BOX	Cool Daylight	6500 K	56 lm/W
927904882701	MASTER PL-C 13W/827/2P 1CT/5X10BOX	Incandescent White	2700 K	69 lm/W
927904883001	MASTER PL-C 13W/830/2P 1CT/5X10BOX	Warm White (WW)	3000 K	69 lm/W
927904884002	MASTER PL-C 13W/840/2P 1CT/5X10BOX	Cool White (CW)	4000 K	69 lm/W

Order Code	Full Product Name	Color Designation	Correlated	
			Color Temperature (Nom)	Luminous Efficacy (rated) (Nom)
927905782701	MASTER PL-C 18W/827/2P 1CT/5X10BOX	Incandescent White	2700 K	67 lm/W
927905783001	MASTER PL-C 18W/830/2P 1CT/5X10BOX	Warm White (WW)	3000 K	67 lm/W
927906184001	MASTER PL-C 26W/840/2P 1CT/5X10BOX	Cool White (CW)	4000 K	68 lm/W
927906186565	MASTER PL-C 26W/865/2P 1CT/5X10BOX	Cool Daylight	6500 K	66 lm/W

Operating and Electrical

Order Code	Full Product Name	Lamp Current (Nom)
927903882701	MASTER PL-C 10W/827/2P 1CT/5X10BOX	0.190 A
927903886502	MASTER PL-C 10W/865/2P 1CT/5X10BOX	0.190 A
927904882701	MASTER PL-C 13W/827/2P 1CT/5X10BOX	0.170 A
927904883001	MASTER PL-C 13W/830/2P 1CT/5X10BOX	0.170 A
927904884002	MASTER PL-C 13W/840/2P 1CT/5X10BOX	0.170 A

Order Code	Full Product Name	Lamp Current (Nom)
927905782701	MASTER PL-C 18W/827/2P 1CT/5X10BOX	0.230 A
927905783001	MASTER PL-C 18W/830/2P 1CT/5X10BOX	0.230 A
927906184001	MASTER PL-C 26W/840/2P 1CT/5X10BOX	0.335 A
927906186565	MASTER PL-C 26W/865/2P 1CT/5X10BOX	0.335 A

Approval and Application

Order Code	Full Product Name	Energy Consumption kWh/	
		1000 h	
927903882701	MASTER PL-C 10W/827/2P 1CT/5X10BOX	13 kWh	
927903886502	MASTER PL-C 10W/865/2P 1CT/5X10BOX	13 kWh	

Order Code	Full Product Name	Energy Consumption kWh/	
		1000 h	
927904882701	MASTER PL-C 13W/827/2P 1CT/5X10BOX	17 kWh	
927904883001	MASTER PL-C 13W/830/2P 1CT/5X10BOX	17 kWh	

MASTER PL-C 2 Pin

Order Code	Full Product Name	Energy Consumption kWh/ 1000 h
927904884002	MASTER PL-C 13W/840/2P 1CT/5X10BOX	17 kWh
927905782701	MASTER PL-C 18W/827/2P 1CT/5X10BOX	22 kWh
927905783001	MASTER PL-C 18W/830/2P 1CT/5X10BOX	22 kWh

Order Code	Full Product Name	Energy Consumption kWh/ 1000 h
927906184001	MASTER PL-C 26W/840/2P 1CT/5X10BOX	32 kWh
927906186565	MASTER PL-C 26W/865/2P 1CT/5X10BOX	32 kWh

