

NYLON CABLE GLAND PG TYPE

Thread special: PG

Material: Part sealing nut, body, locknut are made of UL approved nylon PA66, parts seal and washer are made of NBR

Working temper: -40°C to 100°C in static state, instantaneous heat resistance up to 120°C
-20°C to 80°C in dynamic state, instantaneous heat resistance up to 100°C

Characteristic: Special design of clamping die and rubber part, large range in clamping cable, ultra-strong stretching resistance, waterproof, dustproof, and high ability to resist salt, acid, alkali, alcohol, grease, and general solvent

Color select: Red (R), Yellow (Y), Blue (BL), Green (G), Gray (GR), Black (B), Grayish-white (GRW)



Model	Thread size	Cable range (mm)	Thread OD AG (mm)	Thread length GL (mm)	Spanner size (mm)
PG-PA66-07-6.5	PG7	3 - 6.5	12.5	9	18/16
PG-PA66-07-5	PG7	2 - 5	12.5	9	18/16
PG-PA66-09-8	PG9	4 - 8	15.2	9	22/19
PG-PA66-09-6	PG9	2 - 6	15.2	9	22/19
PG-PA66-11-10	PG11	5 - 10	18.6	9	24/22
PG-PA66-11-7	PG11	3 - 7	18.6	9	24/22
PG-PA66-13.5-11	PG13.5	6 - 11	20.4	10	27/24
PG-PA66-13.5-9	PG13.5	5 - 9	20.4	10	27/24
PG-PA66-16-13	PG16	10 - 13	22.5	10	30/27
PG-PA66-16-12	PG16	7 - 12	22.5	10	30/27
PG-PA66-19-15	PG19	12 - 15	24	10	30/28
PG-PA66-19-12	PG19	10 - 12	24	10	30/28
PG-PA66-21-18	PG21	13 - 18	28.3	12	35/33
PG-PA66-21-16	PG21	9 - 16	28.3	12	35/33
PG-PA66-25-21	PG25	16 - 21	30	12	37/35
PG-PA66-25-18	PG25	13 - 18	30	12	37/35
PG-PA66-29-25	PG29	18 - 25	37	12	45/42
PG-PA66-29-20	PG29	13 - 20	37	12	45/42
PG-PA66-36-32	PG36	22 - 32	47	15	58/52
PG-PA66-36-26	PG36	20 - 26	47	15	58/52
PG-PA66-42-38	PG42	32 - 38	54	18	62/58
PG-PA66-42-31	PG42	25 - 31	54	18	62/58
PG-PA66-48-44	PG48	37 - 44	59.3	18	70/64
PG-PA66-48-35	PG48	29 - 35	59.3	18	70/64
PG-PA66-63-50	PG63	42 - 50	71	30	83/77
PG-PA66-63-40	PG63	32 - 40	71	30	83/77