

PG



Material: Nickel-plated brass
 Claw: PA66 (Nylon) , UL94-V2
 Hermetic seal: NBR, Silicone rubber
 O-Ring: NBR, Silicone rubber
 Protection degree: IP68-10 bar
 Temperature: Static state: -40°C to 100°C ,
 Short time to 120 °C ;
 Dynamic state: -20°C to 80°C ,
 Short time to 100°C

Sealing Nut



Claw



Seal




Body



O-ring



Lock Nut



Specification parameter

Item	Range	Thread Length GL	Thread O.D. AG	Mounting Hole	Joint Length H	Spanner Size
PG7	2-5	6.5	12.5	12.5-12.7	17	14/15
PG7	3-6.5	6.5	12.5	12.5-12.7	17	14/15
PG9	3-6.5	8	15.2	15.2-15.4	19	17/18
PG9	4-8	8	15.2	15.2-15.4	19	17/18
PG11	4-8	8	18.6	18.6-18.8	21	20/21
PG11	5-10	8	18.6	18.6-18.8	21	20/21
PG13.5	5-10	8	20.4	20.4-20.6	22	22/23
PG13.5	6-12	8	20.4	20.4-20.6	22	22/23
PG16	6-12	8	22.5	22.5-22.7	23	24/25
PG16	10-14	8	22.5	22.5-22.7	23	24/25
PG21	12-16	9	28.3	28.3-28.5	27	30
PG21	13-18	9	28.3	28.3-28.5	27	30
PG29	15-22	10	37.0	37.0-37.2	31	40
PG29	18-25	10	37.0	37.0-37.2	31	40
PG36	23-30	11	47.0	47.0-47.2	37	50
PG36	25-33	11	47.0	47.0-47.2	37	50
PG42	30-35	13	54.0	54.0-54.2	37	57
PG42	32-38	13	54.0	54.0-54.2	37	57
PG48	35-40	14	59.3	59.3-59.5	38	64
PG48	37-44	14	59.3	59.3-59.5	38	64