


QT50(M)L-ETN

Ø50mm Ethernet LED Tower Lights



Remote control through internet or local area network



QT50(M)L-ETN series

QT50L-ETN Ø50mm Pole Mount Ethernet Tower Light

Model number	Layer	Voltage	Current	Certificate	Color
QT50L-ETN QT50ML-ETN	1	DC12V DC24V	0.210A 0.110A	CE DC24V only	• R-Red
	2	DC12V DC24V	0.280A 0.150A		• R-Red • G-Green
	3	DC12V DC24V	0.350A 0.190A		• R-Red • A-Amber • G-Green
	4	DC12V DC24V	0.420A 0.230A		• R-Red • A-Amber • G-Green • B-Blue
	5	DC12V DC24V	0.490A 0.270A		• R-Red • A-Amber • G-Green • B-Blue • W-White

Signal Sound Current (Per Layer)

Voltage	DC12V	DC24V
Current	0.220A	0.120A

Wiring Instructions

- Apply properly rated voltage through the POWER CABLE
- Connect the RJ45 connector of the UTP cable into the PC's Ethernet port or router
- External power line : UL1015 AWG18(0.75sq)×2C 400mm
- Power plug will be provided in case of AC type
- UTP cable : Category 5 cable

Customization

- Customized color arrangement available
- Beige color
- LED Strobe, LED simulated revolving module are available upon request
- Customized pole length available
- Wall mount bracket available



Mounting Bracket

Standard	LB18	LW18
Steel	Steel	PC
QZ18	SZ18	QLA18
PC	Al	PC

* Please refer to page 188-193 for detailed dimensions.


Ordering Specification

QT50L-ETN-WS	-	3	-	24	-	RAG	-	QZ18
[Model number]		[Layer]		[Voltage]		[Color]		[Mount bracket]
<ul style="list-style-type: none"> • QT50L-ETN-BZ • QT50L-ETN-WS • QT50L-ETN-WM • QT50L-ETN-WA • QT50ML-ETN-BZ • QT50ML-ETN-WS • QT50ML-ETN-WM • QT50ML-ETN-WA 		<ul style="list-style-type: none"> • 1-1 layer • 2-2 layers • 3-3 layers • 4-4 layers • 5-5 layers 		<ul style="list-style-type: none"> • 12-DC12V • 24-DC24V 		<ul style="list-style-type: none"> • R-Red • A-Amber • G-Green • B-Blue • W-White 		<ul style="list-style-type: none"> • None • Standard • Bracket • -LB18 -LW18 • -QZ18 -SZ18 • -QLA18

* Mount brackets are available for the pole mount type(QT50L-ETN series) only.

QT70(M)L-ETN

Ø70mm Ethernet LED Tower Lights



Remote control through internet or local area network



QT70(M)L-ETN series

QT70L-ETN Ø70mm Pole Mount Ethernet Tower Light

Model number	Layer	Voltage	Current	Certificate	Color
QT70L-ETN QT70ML-ETN	1	DC12V DC24V	0.210A 0.110A	CE DC24V only	● R-Red
	2	DC12V DC24V	0.290A 0.160A		● R-Red ● G-Green
	3	DC12V DC24V	0.370A 0.210A		● R-Red ● A-Amber ● G-Green
	4	DC12V DC24V	0.450A 0.260A		● R-Red ● A-Amber ● G-Green ● B-Blue
	5	DC12V DC24V	0.530A 0.310A		● R-Red ● A-Amber ● G-Green ● B-Blue ● W-White

Signal Sound Current (Per Layer)

Voltage	DC12V	DC24V
Current	0.220A	0.120A

Wiring Instructions

- Apply properly rated voltage through the POWER CABLE
- Connect the RJ45 connector of the UTP cable into the PC's Ethernet port or router
- External power line : UL1015 AWG18(0.75sq)×2C 400mm
- Power plug will be provided in case of AC type
- UTP cable : Category 5 cable

Customization

- Customized color arrangement available
- Beige color
- LED Strobe, LED simulated revolving module are available upon request
- Customized pole length available
- Wall mount bracket available



Wall Mount Bracket
TWS80

Wall Mount Bracket
TWA80

Mounting Bracket

Standard Steel	LB18 Steel	LW18 PC
QZ18 PC	SZ18 Al	QLA18 PC

※ Please refer to page 188-193 for detailed dimensions.

Ordering Specification

QT70L-ETN-WS	-	3	-	24	-	RAG	-	QZ24
[Model number]		[Layer]		[Voltage]		[Color]		[Mount bracket]
<ul style="list-style-type: none"> • QT70L-ETN-BZ • QT70L-ETN-WS • QT70L-ETN-WM • QT70L-ETN-WA • QT70ML-ETN-BZ • QT70ML-ETN-WS • QT70ML-ETN-WM • QT70ML-ETN-WA 		<ul style="list-style-type: none"> • 1-1 layer • 2-2 layers • 3-3 layers • 4-4 layers • 5-5 layers 		<ul style="list-style-type: none"> • 12-DC12V • 24-DC24V 		<ul style="list-style-type: none"> ● R-Red ● A-Amber ● G-Green ● B-Blue ● W-White 		<ul style="list-style-type: none"> • None -Standard • Bracket -LB24 -LW24 -QZ24 -SZ24 -QLA24

※ Mount brackets are available for the pole mount type(QT70L-ETN series) only.

ST-ETN/ QT-ETN series

Ethernet LED Tower Lights



Technical Diagram

(Units : mm)

