

# QT70(M)L-ETN

Ø70mm Ethernet LED Tower Lights



Remote control through internet or local area network



QT70(M)L-ETN series

## QT70L-ETN Ø70mm Pole Mount Ethernet Tower Light

Model number	Layer	Voltage	Current	Certificate	Color
QT70L-ETN QT70ML-ETN	1	DC12V DC24V	0.210A 0.110A	CE DC24V only	● R-Red
	2	DC12V DC24V	0.290A 0.160A		● R-Red ● G-Green
	3	DC12V DC24V	0.370A 0.210A		● R-Red ● A-Amber ● G-Green
	4	DC12V DC24V	0.450A 0.260A		● R-Red ● A-Amber ● G-Green ● B-Blue
	5	DC12V DC24V	0.530A 0.310A		● R-Red ● A-Amber ● G-Green ● B-Blue ● W-White

### Signal Sound Current (Per Layer)

Voltage	DC12V	DC24V
Current	0.220A	0.120A

### Wiring Instructions

- Apply properly rated voltage through the POWER CABLE
- Connect the RJ45 connector of the UTP cable into the PC's Ethernet port or router
- External power line : UL1015 AWG18(0.75sq)×2C 400mm
- Power plug will be provided in case of AC type
- UTP cable : Category 5 cable

### Customization

- Customized color arrangement available
- Beige color
- LED Strobe, LED simulated revolving module are available upon request
- Customized pole length available
- Wall mount bracket available



Wall Mount Bracket  
TWS80

Wall Mount Bracket  
TWA80

### Mounting Bracket

Standard  Steel	LB18  Steel	LW18  PC
QZ18  PC	SZ18  Al	QLA18  PC

※ Please refer to page 188-193 for detailed dimensions.

### Ordering Specification

<b>QT70L-ETN-WS</b>	-	<b>3</b>	-	<b>24</b>	-	<b>RAG</b>	-	<b>QZ24</b>
[Model number]		[Layer]		[Voltage]		[Color]		[Mount bracket]
<ul style="list-style-type: none"> <li>• QT70L-ETN-BZ</li> <li>• QT70L-ETN-WS</li> <li>• QT70L-ETN-WM</li> <li>• QT70L-ETN-WA</li> <li>• QT70ML-ETN-BZ</li> <li>• QT70ML-ETN-WS</li> <li>• QT70ML-ETN-WM</li> <li>• QT70ML-ETN-WA</li> </ul>		<ul style="list-style-type: none"> <li>• 1-1 layer</li> <li>• 2-2 layers</li> <li>• 3-3 layers</li> <li>• 4-4 layers</li> <li>• 5-5 layers</li> </ul>		<ul style="list-style-type: none"> <li>• 12-DC12V</li> <li>• 24-DC24V</li> </ul>		<ul style="list-style-type: none"> <li>● R-Red</li> <li>● A-Amber</li> <li>● G-Green</li> <li>● B-Blue</li> <li>● W-White</li> </ul>		<ul style="list-style-type: none"> <li>• None</li> <li>-Standard</li> <li>• Bracket</li> <li>-LB24 -LW24</li> <li>-QZ24 -SZ24</li> <li>-QLA24</li> </ul>

※ Mount brackets are available for the pole mount type(QT70L-ETN series) only.

# ST-ETN/ QT-ETN series

Ethernet LED Tower Lights



## Technical Diagram

(Units : mm)

