

SESA series



Explosion proof warning light and electric horn combinations with sound output of Max 118dB



SESLR



SESAL



SEAS

Explosion Proof Warning/ Signal Light and Max 118dB Electric Horn Combinations

Qlightec



Common Specifications(SESALR/ SESAL/ SEAS/ SESA)

- Large explosion proof warning light and electric horn combinations
- A variety of light sources and sound selections to fit your sophisticated application needs
- Aluminum housing provides excellent durability
- Fully enclosed structure with protection rating of IP66
- Integrated housing and terminal box model
- Sound volume : Max 118dB at 1m(Volume adjustable)
- Standard housing color : MUNSELL No. 7.5BG 7/2
- Cable entry : 1/2" NPT
- Materials : Lens-Tempered glass, Filter-PC, Housing-Al, Protection cage-SUS316L, Reflector for LED type-PC/Reflector for bulb type-Heat resistant ABS
- Certificates : IECEx, ATEX, NEPSI, KIMM, KOSHA, ABS, CCS, KR, CCC(F)
- Protection rating :
 - IECEx - Ex d II C T6 Gb, IP66
 - ATEX - Ex II 2G Ex d IIC T6, IP66
 - NEPSI, KIMM, KOSHA - Ex d IIC T6, IP66
- Ambient operating temperature : -40°C ≤ Tamb ≤ +60°C



SESALR LED Revolving Warning Light and Electric Horn Combination

- Excellent omni-directional visibility with LED light collecting system and special multifaceted reflector
- Revolving speed : 120-140RPM

Model number	Voltage	Current	Sound pattern and volume	Certificates	Weight	Color
SESLR	DC12V	2.633A	<ul style="list-style-type: none"> • WS-5 Warning sounds : 118dB • WP-5 Special warning sounds : 118dB • WM-5 Melodies : 118dB • WA-5 Alarms : 115dB • WV-5 Customizable voices : 113dB 	IECEx Ex ATEX NEPSI KIMM KC ABS CCS KR CCC	8.31kg	<ul style="list-style-type: none"> ● R-Red ● A-Amber ● G-Green ● B-Blue
	DC24V	1.288A			8.31kg	
	AC110V	0.308A			7.92kg	
	AC220V	0.154A			7.92kg	



SESAL LED Steady/ Flashing Signal Light and Electric Horn Combination

- Long product lifetime with the application of a high intensity LED light source
- Suitable for locations where bulb replacement is inconvenient
- Built in switch for steady/flashing selection
- Flashing rate : 60-80 flashes/min

Model number	Voltage	Current	Sound pattern and volume	Certificates	Weight	Color
SESAL	DC12V	2.511A	<ul style="list-style-type: none"> • WS-5 Warning sounds : 118dB • WP-5 Special warning sounds : 118dB • WM-5 Melodies : 118dB • WA-5 Alarms : 115dB • WV-5 Customizable voices : 113dB 	IECEx Ex ATEX NEPSI KIMM KC ABS CCS KR CCC	8.42kg	<ul style="list-style-type: none"> ● R-Red ● A-Amber ● G-Green ● B-Blue
	DC24V	1.222A			8.42kg	
	AC110V	0.286A			9.02kg	
	AC220V	0.143A			9.02kg	



SEAS Xenon Lamp Strobe Signal Light and Electric Horn Combination

- Lamp connector fastening structure allows for convenient lamp replacement
- High efficiency strobe light offers excellent visibility for long distances
- Flashing rate : 60-80 flashes/min

Model number	Voltage	Current	Spec	Bulb Standard	Parts no	Sound pattern and volume	Certificates	Weight	Color
SEAS	DC12V	2.933A	200V-550V	EUB0641-1A(G) U Type	48	<ul style="list-style-type: none"> • WS-5 Warning sounds : 118dB • WP-5 Special warning sounds : 118dB • WM-5 Melodies : 118dB • WA-5 Alarms : 115dB • WV-5 Customizable voices : 113dB 	IECEx Ex ATEX NEPSI KIMM KC ABS CCS KR CCC	8.45kg	<ul style="list-style-type: none"> ● R-Red ● A-Amber ● G-Green ● B-Blue
	DC24V	1.411A						8.45kg	
	AC110V	0.360A						8.86kg	
	AC220V	0.220A						8.86kg	



Warning/
Signal/
Stackable



Signal &
Electric Horn/
Speakers



Vessels and
Heavy-Duty
Equipment



Explosion
Proof



Warning
Light Bar



Aviation
Obstruction
Lights



Signal Tower
Lights



USB/ETN
Signal Tower
Lights



Wireless
Network
System



Electric Horn/
Speakers



Industrial
LED Lights

SESA series



Explosion Proof Warning/ Signal Light and Max 118dB Electric Horn Combinations

Qlightec



SESA

SESA Bulb Revolving Warning Light and Electric Horn Combinations


- Excellent diffusion effect with special multifaceted reflector
- Revolving speed : 120-140RPM

Model number	Voltage	Current	Bulb			Sound pattern and volume	Certificates	Weight	Color
			Spec	Standard	Parts no				
SESA	DC12V	3.755A	12V15W G23 15S	17		• WS-5 Warning sounds :118dB • WP	IECEx ATEX KIAMS KC ABS CCS KR CCCf	8.57kg	
	DC24V	1.788A	24V15W G23 15S	18		-5 Special warning sounds :118dB • WM-5 Melodies : 118dB • WA-5 Alarms : 115dB • WV -5 Customizable voices : 113dB		8.57kg	● R-Red ● A-Amber
	AC110V	0.422A	12V15W G23 15S	17				9.27kg	● G-Green
	AC220V	0.211A	12V15W G23 15S	17				9.27kg	● B-Blue

Technical Diagram


(Units : mm)

SESALR/ SESAL/ SESAS/ SESA




Sound Selection Instructions and Wiring

- Standard type : Select sound using the switch inside of the unit. When you turn on the dip switch for each channel, designated sound is played.



- Customization : External contact(LC)
Customization of signal line threading can be choice between external contact and transistor which can be fit for control unit.

SESA SERIES-DC/AC



- SESA, SESALR : Black output line is negative(-)



Customization

- Explosion proof cable gland attached type available
(Standard type does not come with explosion proof cable gland)
- 2 way cable entries
- Customized cable entry (3/4" NPT, M20×1.5, M25×1.5) available
- ATEX compliant products
- IECEx compliant products

Ordering Specification

SESA	-	WS	-	220	-	R
[Model number]		[Sound]		[Voltage]		[Color]
• SESALR		• WS-Warning sounds		• 12-DC12V		● R-Red
• SESAL		• WP-Special warning sounds		• 24-DC24V		● A-Amber
• SESAS		• WM-Melodies		• 110-AC110V		● G-Green
• SESA		• WA-Alarms		• 220-AC220V		● B-Blue
		• WV-Customizable sounds				